NASA/TM-2000-209891, Vol. 177



Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall, Editor

Volume 177 BOREAS TE-18, 30-m, Radiometrically Rectified Landsat TM Imagery

F.G. Hall and D. Knapp

National Aeronautics and Space Administration

Goddard Space Flight Center Greenbelt, Maryland 20771

The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and mission, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION.
 English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at http://www.sti.nasa.gov/STI-homepage.html
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:
 NASA Access Help Desk
 NASA Center for AeroSpace Information
 7121 Standard Drive

Hanover, MD 21076-1320

NASA/TM-2000-209891, Vol. 177



Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall, Editor

Volume 177 BOREAS TE-18, 30-m, Radiometrically Rectified Landsat TM Imagery

Forrest G. Hall, NASA Goddard Space Flight Center David Knapp, Raytheon ITSS, NASA Goddard Space Flight Center Greenbelt, Maryland

National Aeronautics and Space Administration

Goddard Space Flight Center Greenbelt, Maryland 20771

	Available from:	
NIACA Contourfour Armong units of		Notional Tasks: -1 Informed C
NASA Center for AeroSpace Information		National Technical Information Service
7121 Standard Drive		5285 Port Royal Road
Hanover, MD 21076-1320		Springfield, VA 22161
Drica Codo: A17		Dring Code, A10
Price Code: A17		Price Code: A10

BOREAS TE-18, 30-m, Radiometrically Rectified Landsat TM Imagery

Forrest G. Hall, David Knapp

Summary

The BOREAS TE-18 team used a radiometric rectification process to produce standardized DN values for a series of Landsat TM images of the BOREAS SSA and NSA in order to compare images that were collected under different atmospheric conditions. The images for each study area were referenced to an image that had very clear atmospheric qualities. The reference image for the SSA was collected on 02-Sep-1994, while the reference image for the NSA was collected on 21-Jun-1995. The 23 rectified images cover the period of 07-Jul-1985 to 18-Sep-1994 in the SSA and from 22-Jun-1984 to 09-Jun-1994 in the NSA. Each of the reference scenes had coincident atmospheric optical thickness measurements made by RSS-11. The radiometric rectification process is described in more detail by Hall et al. (1991). The original Landsat TM data were received from CCRS for use in the BOREAS project. The data are stored in binary image-format files.

Due to the nature of the radiometric rectification process and copyright issues, these full-resolution images may not be publicly distributed. However, a spatially degraded 60-m resolution version of the images is available on the BOREAS CD-ROM series. See Sections 15 and 16 for information about how to possibly acquire the full resolution data. Information about the full-resolution images is provided in an inventory listing on the CD-ROMs.

Table of Contents

- 1) Data Set Overview
- 2) Investigator(s)
- 3) Theory of Measurements
- 4) Equipment
- 5) Data Acquisition Methods
- 6) Observations
- 7) Data Description
- 8) Data Organization
- 9) Data Manipulations
- 10) Errors
- 11) Notes
- 12) Application of the Data Set
- 13) Future Modifications and Plans
- 14) Software
- 15) Data Access
- 16) Output Products and Availability
- 17) References
- 18) Glossary of Terms
- 19) List of Acronyms
- 20) Document Information

1. Data Set Overview

1.1 Data Set Identification

BOREAS TE-18, 30-m, Radiometrically Rectified Landsat TM Imagery

1.2 Data Set Introduction

The Terrestrial Ecology (TE)-18 team used a radiometric rectification process (Hall et al., 1991) to produce standardized digital number (DN) values for a series of Landsat Thematic Mapper (TM) images of the BOReal Ecosystem-Atmosphere Study (BOREAS) Southern Study Area (SSA) and Northern Study Area (NSA). The processing was performed in order to compare images that were collected under different atmospheric conditions. The images for each study area were referenced to an image that had very clear atmospheric qualities. The reference image for the SSA was collected on 02-Sep-1994, while the reference image for the NSA was collected on 21-Jun-1995. The images that were rectified range in date from 07-Jul-1985 to 18-Sep-1994 in the SSA and from 22-Jun-1984 to 09-Jun-1994 in the NSA. Each of the reference scenes had coincident atmospheric optical thickness measurements made by Remote Sensing Science (RSS)-11. The original Landsat TM data were received from the Canada Centre for Remote Sensing (CCRS) for use in the BOREAS project.

1.3 Objective/Purpose

This data product was created in order to provide scientists with a set of images that could be compared as if they were collected under the same atmospheric and illumination conditions. The radiometric rectification process was used to standardize the images for these differences so that the remaining differences in the imagery would be a result of real change in the vegetation.

1.4 Summary of Parameters

The images contain DN values that were adjusted to the following reference scenes:

- SSA (WRS Path/Row 37/22-23) acquired 02-Sep-1994
- NSA (WRS Path/Row 33/21) acquired 21-Jun-1995

1.5 Discussion

Use and distribution of the full-resolution radiometrically rectified Landsat TM images are subject to copyright restrictions. CCRS and Radarsat International (RSI) granted permission to BOREAS to create and distribute spatially degraded 60-m versions of the images on the BOREAS CD-ROM series. The full-resolution images may not be available for public access. Please see Sections 15 and 16 for further details. TE-18 created the radiometrically rectified imagery by:

- Extracting pertinent header information from the level-3s or 3p image product.
- Performing radiometric rectification as described by Hall et al. (1991).
- Reviewing the image bands for correctness.
- Writing the American Standard Code for Information Interchange (ASCII) header file and six image bands to tape.

1.6 Related Data Sets

BOREAS RSS-11 Ground Network of Sun Photometer Measurements

BOREAS TE-18, 60-m, Radiometrically Rectified Landsat TM Imagery

BOREAS Level-3s Landsat TM Imagery: Scaled At-sensor Radiance in LGSOWG Format

BOREAS Level-3b Landsat TM Imagery: At-sensor Radiance in BSQ Format

BOREAS Level-3p Landsat TM Imagery: Geocoded and Scaled At-sensor Radiance

BOREAS Level-3s SPOT Imagery: Scaled At-sensor Radiance in LGSOWG Format

2. Investigator(s)

2.1 Investigator(s) Name and Title

Dr. Forrest G. Hall NASA GSFC

2.2 Title of Investigation

Regional-Scale Carbon Flux from Modeling and Remote Sensing

2.3 Contact Information

Contact 1:

Dr. Forrest G. Hall Code 923 NASA GSFC Greenbelt, MD 20771 (301) 286-2974 (301) 286-0239 (fax) Forrest.Hall@gsfc.nasa.gov

Contact 2:

David Knapp Raytheon ITSS Code 923 NASA GSFC Greenbelt, MD 20771 (301) 286-1424 (301) 286-0239 (fax) David.Knapp@gsfc.nasa.gov

3. Theory of Measurements

The Landsat series of satellites began with the Earth Resources Technology Satellite (ERTS-1) launched in July 1972. This satellite was renamed Landsat 1 in 1975 to reflect its primary use as a land resource observatory. Through its onboard instruments, Landsat monitors Earth's mountain ranges, deserts, forests, and crops by measuring the light waves they reflect.

The second generation of Landsat satellites (4 and 5) marked a significant advance in remote sensing through the addition of the more sophisticated TM sensor, with higher spectral and spatial resolution, and faster data processing at a highly automated data processing facility at the National Aeronautics and Space Administration (NASA) Goddard Space Flight Center (GSFC) in Greenbelt, MD. For BOREAS, the CCRS receiving station in Prince Albert, Saskatchewan, collected the raw data. Processing of the raw data to the imagery used as input for the BOREAS level-3a processing was performed with the Geocoded Image Correction System (GICS; Friedel, 1992) at the CCRS facility in Ottawa, Canada.

As Landsat's instrument mirrors scan Earth's surface, light enters the instrument optics, where it is focused on specially calibrated detector arrays. Onboard electronics encode the detector voltage as binary digits or bits. These digital image data are then relayed back to Earth to be processed into film and Computer-Compatible Tape (CCT) products, which are subsequently used for Earth resources analysis.

The use of retrospective Landsat data presents considerable problems when it is necessary to account for the effects of sensor, atmosphere, and illumination differences over years or among acquisition dates within a year. For this reason, this data product was produced using the radiometric rectification procedure described by Hall et al. (1991). Radiometric rectification consists of two major components:

- One component identifies radiometric control sets, i.e., scene landscape elements that have the same mean reflectance between acquisition dates.
- The second component rectifies the images using a linear transformation whose coefficients force the means of the radiometric control sets to be equal.

4. Equipment

4.1 Sensor/Instrument Description

The TM sensor system records radiation from seven bands in the electromagnetic spectrum. It has a telescope that directs the incoming radiant flux obtained along a scan line through a scan line collector to the visible and near-infrared focal plane, or to the mid-infrared and thermal-infrared cooled focal plane. The detectors for the visible and near-infrared bands (1 to 4) are four staggered linear arrays, each containing 16 silicon detectors. The two mid-infrared detectors are 16 indium-antimonide cells in a staggered linear array, and the thermal-infrared detector is a four-element array of mercury-cadmium-telluride cells. The spectral regions, band widths, and primary use of each channel are given in the following table:

Channel	Wavelength (µm)	Primary Use
1	0.451 - 0.521	Coastal water mapping, soil vegetation
		differentiation, deciduous/coniferous
		differentiation.
2	0.526 - 0.615	Green reflectance by healthy vegetation.
3	0.622 - 0.699	Chlorophyll absorption for plant species
		differentiation.
4	0.771 - 0.905	Biomass surveys, water body delineation.
5	1.564 - 1.790	Vegetation moisture measurement, snow and cloud
		differentiation.
6	10.450 - 12.460	Plant heat stress measurement, other thermal
		mapping.
7	2.083 - 2.351	Hydrothermal mapping.

Note: Channel 6 is not included in this radiometrically rectified data set.

4.1.1 Collection Environment

The BOREAS Landsat TM level-3s and -3p images were acquired through the CCRS and used to create this radiometrically rectified product. Radiometric corrections and systematic geometric corrections are applied to produce the images in a path-oriented, systematically corrected form. The images in the radiometrically rectified data product were extracted as subsets from the original BOREAS Landsat full TM scenes. The ground resolution of the images is 30 m for bands 1, 2, 3, 4, 5, and 7 at nadir. The pixel values of the images can range from 0 to 255. This allows each pixel to be stored in a single-byte field. The level-3s and level-3p images were processed through the GICS. The Landsat satellite orbits Earth at an altitude of 705 km.

4.1.2 Source/Platform

Although the majority of the BOREAS Landsat TM imagery was acquired by the instrument onboard Landsat-5, some images were acquired from the sensor onboard the Landsat-4 satellite.

4.1.3 Source/Platform Mission Objectives

The Landsat TM is designed to respond to and measure both reflected and emitted Earth surface radiation to enable the investigation, survey, inventory, and mapping of Earth's natural resources.

4.1.4 Key Variables

Reflected radiation, emitted radiation, temperature.

4.1.5 Principles of Operation

The TM is a scanning optical sensor operating in the visible and infrared wavelengths. It contains a scan mirror assembly that directly projects the reflected Earth radiation onto detectors arrayed in two focal planes. The TM achieves better image resolution, sharper color separation, and greater in-flight geometric and radiometric accuracy for seven spectral bands simultaneously than the previous generation Landsat sensor, the MultiSpectral Scanner (MSS). Data collected by the sensor are beamed back to ground receiving stations for processing.

4.1.6 Sensor/Instrument Measurement Geometry

The TM sensor depends on the forward motion of the spacecraft for the along-track scan and uses a moving mirror assembly to scan in the cross-track direction (perpendicular to the spacecraft). The instantaneous field of view (IFOV) for each detector from bands 1-5 and band 7 is equivalent to a 30-m square when projected to the ground at nadir.

4.1.7 Manufacturer of Sensor/Instrument

NASA GSFC

Greenbelt, MD 20771

Santa Barbara Remote Sensing (SBRS) 75 Coromar Dr. Goleta, CA 93117

4.2 Calibration

The internal calibrator, a flex-pivot-mounted shutter assembly, is synchronized with the scan mirror, oscillating at the same 7-Hz frequency. During the turnaround period of the scan mirror, the shutter introduces the calibration source energy and a black direct-current restoration surface into the 100-detector field of view (FOV).

The calibration signals for bands 1-5 and 7 are derived from three regulated tungsten-filament lamps. The method for transmitting radiation to the moving calibration shutter allows the tungsten lamps to provide radiation independently and to contribute proportionately to the illumination of all detectors.

4.2.1 Specifications

-	Radiometric			
Band	Sensitivity [NE(dP)]*			
1	0.8%			
2	0.5%			
3	0.5%			
4	0.5%			
5	1.0%			
7	2.4%			
Ground IFOV	30 m (Bands 1-5, 7)			
Avg. altitude	699.6 km			
Data rate	85 Mbps			
Quantization level	ls 256			
Orbit angle	8.15 degrees			
Orbital nodal peri	lod 98.88 minutes			
Scan width	185 km			
Scan angle	14.9 degrees			
Image overlap	7.6%			

Note: The radiometric sensitivities are the noise-equivalent (NE) reflectance differences for the reflective channels expressed as percentages [NE(dP)].

4.2.1.1 Tolerance

The TM channels were designed for an NE differential represented by the radiometric sensitivity shown in Section 4.2.1.

4.2.2 Frequency of Calibration

The absolute radiometric calibration between bands on the TM sensor is maintained by using internal calibrators located between the telescope and the detectors that are sampled at the end of a scan.

4.2.3 Other Calibration Information

To reduce "striping," relative within-band radiometric calibration is provided by a scene-based procedure called histogram equalization. Because of the absolute accuracy and relative precision of this calibration scheme, it is assumed that any changes in the optics of the primary telescope or the "effective radiance" from the internal calibrator lamps are insignificant in comparison to the changes in detector sensitivity and electronic gain and bias with time and that the scene-dependent sampling is sufficiently precise for the required within-scan destriping from histogram equalization.

Each TM reflective band and the internal calibrator lamps were calibrated prior to launch using lamps in integrating spheres that were in turn calibrated against lamps traceable to calibrated National Bureau of Standards lamps. The absolute radiometric calibration constants in the "short-term" and "long-term" parameter files used for ground processing were modified after launch if there was an inconsistency within or between bands, a change in the inherent dynamic range of the sensors, or a desire to make quantized and calibrated values from one sensor match those from another.

The radiometric rectification process adjusted the DNs of the various images to the reference images of the SSA or NSA, amounting to calibration of the images to one of these two reference images. If the user wishes to compute surface reflectance for bands 3, 4, and 5 for any of these images, the following parameters should be used. These parameters were determined using aerosol optical thickness measurements at the time these reference scenes were collected. Refer to Markham et al. (1992) for more information on how to determine and use these parameters to compute surface reflectance.

NSA (Reference I	mage: 21	-Jun-1	995, Pat	h/Row 3	3/21)	
Band	1	2	3	4	5	7
Gain	0.6024	1.175	1 0.8058	0.8145	0.1081	0.0570
Offset	-1.52	-2.84	-1.17	-1.51	-0.37	-0.15
Spherical Albedo	*	*	0.05796	0.03068	0.00621	*
Path Radiance	*	*	0.0215	0.00943	0.00117	*
Gaseous Transmission	n *	*	0.93057	0.90948	0.88199	*
Scattering Transmiss	sion *	*	0.92005	0.9536	0.98479	*

Solar Zenith Angle 38.2°

```
      SSA (Reference Image: 02-Sep-1994, Path/Row 37/22-23)

      Band
      1
      2
      3
      4
      5
      7

      Gain
      0.6024
      1.1751
      0.8058
      0.8145
      0.1081
      0.0570

      Offset
      -1.52
      -2.84
      -1.17
      -1.51
      -0.37
      -0.15

      Spherical Albedo
      *
      *
      0.0597
      0.03094
      0.00592
      *

      Path Radiance
      *
      *
      0.02349
      0.01055
      0.00154
      *

      Gaseous Transmission
      *
      *
      0.92918
      0.92438
      0.90494
      *

      Scattering Transmission
      *
      *
      0.90852
      0.94451
      0.98023
      *

Solar Zenith Angle
```

Note: The atmospheric parameters were not determined as part of the TE-18 research for bands 1, 2, and 7.

For a given band, the at-sensor radiance of a pixel can be computed with the following equation:

At-sensor radiance = DN * Gain + Offset

5. Data Acquisition Methods

The BOREAS Landsat TM level-3s and -3p images that were used to create this product were acquired through the CCRS. Radiometric corrections and systematic or precision geometric corrections are applied to produce the images in a path-oriented form. A full TM image contains 6,920 pixels in each of 5,728 lines (see Section 11.2). The images in this data set are subsets of the full images covering the NSA or SSA. The pixel values of the images can range from 0 to 255. This allows each pixel to be stored in a single-byte field.

6. Observations

6.1 Data Notes

None.

6.2 Field Notes

Not applicable.

7. Data Description

7.1 Spatial Characteristics

7.1.1 Spatial Coverage

The Landsat TM images generally cover the SSA and the NSA, which are located in the southwest and northeast portions of the BOREAS region (Sellers and Hall, 1994). Each image in this data set covers a slightly different area, but each covers all or part of the NSA or SSA.

The North American Datum of 1983 (NAD83) corner coordinates of the SSA are:

	Latitude	Longitude
Northwest	54.321 N	106.228 W
Northeast	54.225 N	104.237 W
Southwest	53.515 N	106.321 W
Southeast	53.420 N	104.368 W

The NAD83 corner coordinates of the NSA are:

	Latitude	Longitude		
Northwest	56.249 N	98.825 W		
Northeast	56.083 N	97.234 W		
Southwest	55.542 N	99.045 W		
Southeast	55.379 N	97.489 W		

7.1.2 Spatial Coverage Map

Not available.

7.1.3 Spatial Resolution

The pixel resolution is approximately 30 meters at nadir.

7.1.4 Projection

The Landsat TM images are in a Universal Transverse Mercator (UTM) projection based on the NAD83. However, these images are not precisely registered in this projection. Any comparison of these images will require coregistration by the user. The level-3a georeferenced Landsat TM data can be used to create georeferenced images from these radiometrically rectified data.

7.1.5 Grid Description

The grid spacing for each pixel in the Landsat TM images is 30 m in the UTM projection.

7.2 Temporal Characteristics

7.2.1 Temporal Coverage

This data set contains 23 images collected from 22-Jun-1984 to 18-Sep-1994.

7.2.2 Temporal Coverage Map

The following two lists provide dates for all the radiometrically rectified TM images that are available from BOREAS.

Date	Study Area
07-Jul-1985	SSA
11-Aug-1986	SSA
30-Aug-1987	SSA
04-Sep-1989	SSA
06-Aug-1990	SSA
05-May-1991	SSA
06-Jun-1991	SSA
24-Jul-1991	SSA
09-Aug-1991	SSA
10-Sep-1991	SSA
07-Jun-1994	SSA
23-Jun-1994	SSA
25-Jul-1994	SSA
18-Sep-1994	SSA
Date	Study Area
22-Jun-1984	NSA
19-Aug-1985	NSA
15-Aug-1986	NSA
01-Jun-1988	NSA
08-Jun-1988	NSA
20-Aug-1988	NSA
05-Sep-1988	NSA
25-Jul-1990	NSA
09-Jun-1994	NSA

7.2.3 Temporal Resolution

The strategy for the radiometrically rectified images was to obtain the best temporal sequence of images over 10 years and to get good coverage of the growing season in one particular year. The tables in Section 7.2.2 reflect this strategy.

7.3 Data Characteristics

7.3.1 Parameter/Variable

The parameters contained in the data files on the CD-ROM are:

Column Name

SPATIAL_COVERAGE

DATE_OBS
START_TIME
END_TIME
PLATFORM
INSTRUMENT
NUM_BANDS
BAND_QUALITY
CLOUD_COVER
PATH_NUM
ROW_NUM

ROW_NUM
PLATFORM_ALTITUDE
MIN_SOLAR_ZEN_ANG
MAX_SOLAR_ZEN_ANG
MIN_SOLAR_AZ_ANG
MAX_SOLAR_AZ_ANG
CRTFCN_CODE

7.3.2 Variable Description/Definition

The descriptions of the parameters contained in the data files on the CD-ROM are:

Column Name	Description
SPATIAL_COVERAGE	The general term used to denote the spatial area over which the data were collected.
DATE_OBS	The date on which the data were collected.
START_TIME	The starting Greenwich Mean Time (GMT) for the data collected.
END_TIME	The ending Greenwich Mean Time (GMT) for the data collected.
PLATFORM	The object (e.g., satellite, aircraft, tower, person) that supported the instrument.
INSTRUMENT	The name of the device used to make the measurements.
NUM_BANDS	The number of spectral bands in the data.
BAND_QUALITY	The data analyst's assessment of the quality of the spectral bands in the data.
CLOUD_COVER	The data analyst's assessment of the cloud cover that exists in the data.
PATH_NUM	For Landsat and SPOT, the sequential number given to the orbital paths trending from northeast to southwest and extending around the earth.
ROW_NUM	For Landsat and SPOT, the sequential number given to the nominal scene acquisition points along the orbital paths which trend from northeast to southwest.

PLATFORM_ALTITUDE The nominal altitude of the data collection

platform above the target.

MIN_SOLAR_ZEN_ANG The minimum angle from the surface normal

(straight up) to the sun during the data

collection.

(straight up) to the sun during the data

collection.

MIN_SOLAR_AZ_ANG The minimum azimuthal direction of the sun

during data collection expressed in clockwise

increments from North.

MAX_SOLAR_AZ_ANG The maximum azimuthal direction of the sun

during data collection expressed in clockwise

increments from North.

CRTFCN CODE The BOREAS certification level of the data.

Examples are CPI (Checked by PI), CGR (Certified by Group), PRE (Preliminary), and CPI-??? (CPI

but questionable).

7.3.3 Unit of Measurement

The gain and offset values needed to derive at-sensor radiance values vary by band. To obtain at-sensor radiance values in Watts/ $(m^2 * ster * mm)$ use the formula:

At-sensor radiance = DN * Gain + Offset

where the gain and offset values are provided in Section 4.2.3. The measurement units for the parameters contained in the data files on the CD-ROM are:

Column Name	Units
SPATIAL_COVERAGE	[none]
DATE_OBS	[DD-MON-YY]
START_TIME	[HHMM GMT]
END_TIME	[HHMM GMT]
PLATFORM	[none]
INSTRUMENT	[none]
NUM_BANDS	[counts]
BAND_QUALITY	[none]
CLOUD_COVER	[none]
PATH_NUM	[unitless]
ROW_NUM	[unitless]
PLATFORM_ALTITUDE	[meters]
MIN_SOLAR_ZEN_ANG	[degrees]
MAX_SOLAR_ZEN_ANG	[degrees]
MIN_SOLAR_AZ_ANG	[degrees]
MAX_SOLAR_AZ_ANG	[degrees]
CRTFCN_CODE	[none]

7.3.4 Data SourceThe sources of the parameter values contained in the data files on the CD-ROM are:

Column Name	Data Source
SPATIAL_COVERAGE	[Determined by BORIS software from latitude and longitude information contained on the level-3s data files.]
DATE_OBS	[Determined by BORIS software from data and time information contained on the level-3s data files.]
START_TIME	[Determined by BORIS software from data and time information contained on the level-3s data files.]
END_TIME	[Determined by BORIS software from data and time information contained on the level-3s data files.]
PLATFORM	[Determined by BORIS software from platform information contained on the level-3s data files.]
INSTRUMENT	[Constant software value]
NUM_BANDS	[Determined by BORIS software from processing of the data files.]
BAND_QUALITY	[Assessed by BORIS personnel from viewing the image.]
CLOUD_COVER	[Assessed by BORIS personnel from viewing the image.]
PATH_NUM	[Determined by BORIS software from location information contained on the level-3s data files.]
ROW_NUM	[Determined by BORIS software from location information contained on the level-3s data files.]
PLATFORM_ALTITUDE	[Determined by BORIS software from platform information contained on the level-3s data files.]
MIN_SOLAR_ZEN_ANG	[Calculated with software from latitude and longitude and time information]
MAX_SOLAR_ZEN_ANG	[Calculated with software from latitude and longitude and time information]
MIN_SOLAR_AZ_ANG	[Calculated with software from latitude and longitude and time information]
MAX_SOLAR_AZ_ANG	[Calculated with software from latitude and longitude and time information]
CRTFCN_CODE	[Assigned by BORIS based on processing.]

7.3.5 Data Range

The following table gives information about the parameter values found in the data files on the CD-ROM.

	Minimum	Maximum	Missng	Unrel	Below	Data
	Data	Data	Data	Data	Detect	Not
Column Name	Value	Value			Limit	Cllctd
SPATIAL_COVERAGE	N/A	N/A	None	None	None	None
DATE_OBS	22-JUN-84	18-SEP-94	None	None	None	None
START_TIME	1652	1728	None	None	None	None
END_TIME	1652	1728	None	None	None	None
PLATFORM	LANDSAT-5	LANDSAT-5	None	None	None	None
INSTRUMENT	N/A	N/A	None	None	None	None
NUM_BANDS	7	7	None	None	None	None
BAND_QUALITY	N/A	N/A	None	None	None	None
CLOUD_COVER	N/A	N/A	None	None	None	None
PATH_NUM	033	037	None	None	None	None
ROW_NUM	021	022	None	None	None	None
PLATFORM_ALTITUDE	705300	705300	None	None	None	None
MIN_SOLAR_ZEN_ANG	35.8	55.2	None	None	None	None
MAX_SOLAR_ZEN_ANG	35.8	55.2	None	None	None	None
MIN_SOLAR_AZ_ANG	137.5	152.3	None	None	None	None
MAX_SOLAR_AZ_ANG	137.5	152.3	None	None	None	None
CRTFCN_CODE	CPI	CPI	None	None	None	None

Minimum Data Value -- The minimum value found in the column.

Maximum Data Value -- The maximum value found in the column.

Missng Data Value -- The value that indicates missing data. This is used to indicate that an attempt was made to determine the parameter value, but the attempt was unsuccessful.

Unrel Data Value -- The value that indicates unreliable data. This is used to indicate an attempt was made to determine the parameter value, but the value was deemed to be unreliable by the analysis personnel.

Below Detect Limit -- The value that indicates parameter values below the instruments detection limits. This is used to indicate that an attempt was made to determine the parameter value, but the analysis personnel determined that the parameter value was below the detection limit of the instrumentation.

Data Not Cllctd -- This value indicates that no attempt was made to determine the parameter value. This usually indicates that BORIS combined several similar but not identical data sets into the same data base table but this particular science team did not measure that parameter.

Blank -- Indicates that blank spaces are used to denote that type of value. N/A -- Indicates that the value is not applicable to the respective column. None -- Indicates that no values of that sort were found in the column.

7.4 Sample Data Record

The following are wrapped versions of records from the inventory file on the CD-ROM.

```
SPATIAL_COVERAGE, DATE_OBS, START_TIME, END_TIME, PLATFORM, INSTRUMENT, NUM_BANDS, BAND_QUALITY, CLOUD_COVER, PATH_NUM, ROW_NUM, PLATFORM_ALTITUDE, MIN_SOLAR_ZEN_ANG, MAX_SOLAR_ZEN_ANG, MIN_SOLAR_AZ_ANG, MAX_SOLAR_AZ_ANG, CRTFCN_CODE 'NSA', 22-JUN-84, 1701, 1701, 'LANDSAT-5', 'THEMATIC MAPPER', 7, 'GOOD', '50%', '033', '021', 705300.0, 36.5, 36.5, 142.8, 142.8, 'CPI' 'SSA', 07-JUL-85, 1728, 1728, 'LANDSAT-5', 'THEMATIC MAPPER', 7, 'AVERAGE', '10%', '037', '022', 705300.0, 35.8, 35.8, 141.4, 141.4, 'CPI'
```

8. Data Organization

8.1 Data Granularity

The smallest unit of data that can be ordered from these radiometrically rectified data is a single image.

8.2 Data Format(s)

The CD-ROM inventory listing file consists of numerical and character fields of varying length separated by commas. The character fields are enclosed with single apostrophe marks. There are no spaces between the fields.

Each image in this data set consists of seven files, one ASCII header file and 6 binary image files.

FILE 1 (80 byte ASCII text records)

 Header file indicating acquisition date and time, Path/Row, Pixels per line, and Number of lines.

FILES 2 - 7 (A band-sequential (BSQ) set of files containing radiometrically rectified Landsat TM bands 1 to 5 and 7, respectively.)

- Each pixel value is in units of digital counts (see Section 11.2).
- Each image is oriented so that pixel 1, line 1 is in the upper left-hand corner (i.e., northwest) of the screen display. Pixels and lines progress left to right and top to bottom so that pixel n, line n is in the lower right-hand corner.

The characteristics for each image are:

	Number Of	Number Of	
	_	_	_
Date	Pixels	Lines	Study Area
30-Aug-1987	4096	3072	SSA
18-Sep-1994	4096	3072	SSA
04-Sep-1989	4096	3072	SSA
11-Aug-1986	4096	3072	SSA
06-Aug-1990	4096	3072	SSA
07-Jun-1994	2048	3072	SSA
25-Jul-1994	2048	3072	SSA
23-Jun-1994	2048	3072	SSA
07-Jul-1985	4096	3072	SSA
09-Aug-1991	4096	3072	SSA
24-Jul-1991	4096	3072	SSA
06-Jun-1991	4096	3072	SSA
10-Sep-1991	4096	3072	SSA

05-May-1991	4096	3072	SSA
15-Aug-1986	4096	2560	NSA
19-Aug-1985	2668	2560	NSA
20-Aug-1988	4096	2560	NSA
05-Sep-1988	4096	2560	NSA
25-Jul-1990	4096	2560	NSA
22-Jun-1984	4096	2560	NSA
08-Jun-1988	2668	2560	NSA
09-Jun-1994	2668	2560	NSA
01-Jun-1988	4096	2560	NSA

9. Data Manipulations

9.1 Formulae

9.1.1 Derivation Techniques and Algorithms

See Hall et al. (1991).

9.2 Data Processing Sequence

9.2.1 Processing Steps

TE-18 created the radiometrically rectified Landsat TM images by:

- Selecting scenes for the period of interest (mid-1980's to mid-1990's).
- Selecting a clear reference scene for the NSA and SSA.
- For each scene to be rectified, selecting a radiometric control set from the nonvegetated extremes of the Kauth-Thomas (KT) greenness-brightness distribution function. This is done by identifying pixels with both low greenness and low or high brightness extremes.
- Calculating radiometric transformation from the subject image to the reference image. This
 linear function can be determined by finding the mean of the dark targets and the mean of the
 bright targets.
- Processing each band of the image with the derived radiometric transformation, producing a radiometrically rectified image.
- Writing the files to tape.

The selection of a radiometric control set is designed to identify the brightest and darkest scene reflectors whose reflectance can be expected to remain within very narrow ranges over time. This set of landscape elements or pixels does not necessarily occupy the same scene coordinates over time, as do geometric control points for spatial image rectification. Instead, the radiometric control sets are selected to occupy equivalent positions in the radiometric distribution of each image, namely the "nonvegetated" extremes of the two-dimensional distribution function in the KT greenness-brightness plane. The basis for this approach is as follows. We know that if a scene has nonvegetated landscape elements, then they will be represented by pixels that are the "least" green of the KT greenness-brightness histogram for that scene. Such pixels are usually water bodies, bare rock outcrops, roads, or bare fields. Of the image features available for rectification, water and bare rock will have the least variation in reflectance with time. Please refer to Hall et al. (1991) for detailed information about the radiometric rectification process.

9.2.2 Processing Changes None.

9.3 Calculations

9.3.1 Special Corrections/Adjustments

None.

9.3.2 Calculated Variables

None.

9.4 Graphs and Plots

None.

10. Errors

10.1 Sources of Error

Errors could arise in the acquired imagery from location inaccuracy, distortion of lengths, anisomorphism, the instrument's local coherence, and multispectral registrability. Other errors could arise from inherent radiometric imperfections of the sensors.

The rectification transforms will be inexact to the extent that there is noise in the determination of the radiometric control points. Other sources of error can include biases introduced by radiometric control points with reflectance that is not constant from image to image or nonlinearity of the radiance values between images.

10.2 Quality Assessment

10.2.1 Data Validation by Source

Whatever the processing level, the geometric quality of the image depends on the accuracy of the viewing geometry and the ground control points as required to adjust the viewing geometry model. Spectral errors could arise from image-wide signal-to-noise ratio, saturation, cross-talk, spikes, and response normalization caused by change in gain.

10.2.2 Confidence Level/Accuracy Judgment

Assessment of accuracy of the absolute radiometric constants in the original imagery is difficult. The uncertainties in prelaunch and postlaunch updates of the absolute TM calibration constants are nominally specified to be less than 10%. A root mean square summing of known errors in the prelaunch calibration suggests that this may be a reasonable estimate of overall uncertainty in the prelaunch calibration.

There are also known, but as yet uncorrected, effects associated with temperature-dependence of the TM internal calibrator that may be contributing to apparent discontinuous changes at launch and to the continuous changes of gain while in orbit. Additional uncertainties for exoatmospheric reflectances are probably less than 2% in the visible/near-infrared and less than 5% in the shortwave infrared portion of the spectrum as judged by the current differences in estimates of the solar irradiance.

Since the radiometric rectification process derives atmospheric characteristics from another image, it will most likely produce errors that are larger than exist within an image for which the atmospheric optical thickness was measured directly.

10.2.3 Measurement Error for Parameters

Not available.

10.2.4 Additional Quality Assessments

In the original Landsat TM data, the ability to reproduce coincident TM and ground measurements made for five dates at White Sands, NM, to about 5% for bands 1-4 suggests a potential for monitoring sensor change for the system with time. The images were screened for cloud cover before BOREAS Information System (BORIS) processing. The images have a minimum of cloud cover over the study areas.

10.2.5 Data Verification by Data Center

BORIS staff checked the image files by visually inspecting them on a display screen and reading the ASCII header files for correctness.

11. Notes

11.1 Limitations of the Data

Some images had clouds and other atmospheric features that made it difficult to identify targets for radiometric rectification. In cases where the atmosphere is not homogenous across the image, the radiometric rectification may not adequately account for atmospheric variation between images.

11.2 Known Problems with the Data

See Section 11.1.

11.3 Usage Guidance

Please read the entire contents of this document before using the data.

11.4 Other Relevant Information

None.

12. Application of the Data Set

The radiometrically rectified Landsat TM images are useful for anyone interested in high spatial resolution imagery over the entire NSA or SSA.

13. Future Modifications and Plans

None.

14. Software

14.1 Software Description

None.

14.2 Software Access

None.

15. Data Access

The BOREAS radiometrically rectified Landsat TM images are available from the Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC).

15.1 Contact Information

For BOREAS data and documentation please contact:

ORNL DAAC User Services Oak Ridge National Laboratory P.O. Box 2008 MS-6407 Oak Ridge, TN 37831-6407

Phone: (423) 241-3952 Fax: (423) 574-4665

E-mail: ornldaac@ornl.gov or ornl@eos.nasa.gov

15.2 Data Center Identification

Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC) for Biogeochemical Dynamics http://www-eosdis.ornl.gov/.

15.3 Procedures for Obtaining Data

Although the BOREAS radiometrically rectified Landsat TM images are being held in a public archive, copyright restrictions limit the distribution and use of the data. The BOREAS CD-ROM series is publicly available and the spatially-degraded 60-m version of the radiometrically rectified Landsat TM images on the CD-ROMs are available for unrestricted use. However, the other images in the collection are available only to official BOREAS project personnel. Please contact the ORNL DAAC User Services office to get the most recent information.

Users may obtain data directly through the ORNL DAAC online search and order system [http://www-eosdis.ornl.gov/] and the anonymous FTP site [ftp://www-eosdis.ornl.gov/data/] or by contacting User Services by electronic mail, telephone, fax, letter, or personal visit using the contact information in Section 15.1.

15.4 Data Center Status/Plans

The ORNL DAAC is the primary source for BOREAS field measurement, image, GIS, and hardcopy data products. The BOREAS CD-ROM and data referenced or listed in inventories on the CD-ROM are available from the ORNL DAAC.

16. Output Products and Availability

16.1 Tape Products

These data can be made available on 8-mm, Digital Archive Tape (DAT) media.

16.2 Film Products

None.

16.3 Other Products

Although the inventory is contained on the BOREAS CD-ROM set, the actual radiometrically rectified Landsat TM images are not. See Section 15 for information about how to obtain the data.

17. References

17.1 Platform/Sensor/Instrument/Data Processing Documentation

Multispectral Scanner System for ERTS. 1972. HS324-5214. Hughes Aircraft Corporation. Santa Barbara, CA.

User's Guide for Landsat Thematic Mapper Computer-Compatible Tapes. 1985. Earth Observation Satellite Company. Lanham, MD.

17.2 Journal Articles and Study Reports

Byrne, G.F., P.F. Crapper, and K.K. Mayo. 1980. Monitoring land-cover change by principal component analysis of multitemporal Landsat data. Remote Sens. Environ. 10:175-184.

Chavez, P.C., S.C. Guptill, and J.A. Bowell. 1984. Image processing techniques for Thematic Mapper data. Technical Papers. 50th Annual Meeting of the Amer. Soc. of Photogr. 2:728-743.

Crist, E.P. and R.C. Cicone. 1984. Application of the Tasseled Cap concept to simulated Thematic Mapper data. Photogr. Engr. & Rem. Sens. 50:343-352.

Engel, J.L. and O. Weinstein. 1983. The Thematic Mapper: An Overview. IEEE Transactions on Geoscience and Remote Sensing. GE-21:258-265.

Friedel, J. 1992. System description of the Geocoded Image Correction System. Report GC-MA-50-3915, MacDonald Detwiller and Associates, Richmond, B.C.

Hall, F.G., D.E. Strebel, J.E. Nickeson, and S.J. Goetz. 1991. Radiometric Rectification: Toward a Common Radiometric Response Among Multidate, Multisensor Images. Remote Sens. Environ. 35:11-27.

Holmes, R.A. 1984. Advanced sensor systems: Thematic Mapper and beyond. Remote Sens. Environ. 15:213-221.

Kanemasu, E.T., J.L. Heilman, J.O. Bagley, and W.L. Powers. 1977. Using Landsat data to estimate evapotranspiration of winter wheat. Environmental Management. 1:515-520.

Lulla, K. 1983. The Landsat satellites and selected aspects of Physical Geography. Progress in Phy. Geogr. 7:1-45.

Malila, W.A. 1985. Comparison of the Information Contents of Landsat TM and MSS Data. Photogrammetric Engineering and Remote Sensing. 51:1449-1457.

Markham, B.L., R.N. Halthorne, and S.J. Goetz. 1992. Surface reflectance retrieval from satellite and aircraft sensors: Results of sensor and algorithm comparisons during FIFE. Journal of Geophysical Research 97(D17): 18,785-18,795.

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. 2000. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM.

Pollock, R.B. and E.T. Kanemasu. 1979. Estimating leaf-area index of wheat with Landsat data. Remote Sens. Environ. 8:307-312.

Robinov, C.J. 1982. Computation with physical values from Landsat digital data. Photogr. Engr. & Rem. Sens. 48:781-784.

Salomonson, V.V. 1984. Landsat 4 and 5 status and results from Thematic Mapper data analysis. Proceedings. Machine Processing of Remotely Sensed Data Symposium. Lab. for the Applications of Remote Sensing. West Lafayette, IN. p 13-18.

Satterwhite, M.B. 1984. Discriminating vegetation and soils using Landsat MSS and Thematic Mapper bands and band ratios. Technical Papers. 50th Annual Meeting of the Amer. Soc. of Photogr. 2:479-485.

Sellers, P. and F. Hall. 1994. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1994-3.0, NASA BOREAS Report (EXPLAN 94).

Sellers, P. and F. Hall. 1996. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1996-2.0, NASA BOREAS Report (EXPLAN 96).

Sellers, P., F. Hall, and K.F. Huemmrich. 1996. Boreal Ecosystem-Atmosphere Study: 1994 Operations. NASA BOREAS Report (OPS DOC 94).

Sellers, P., F. Hall, and K.F. Huemmrich. 1997. Boreal Ecosystem-Atmosphere Study: 1996 Operations. NASA BOREAS Report (OPS DOC 96).

Sellers, P., F. Hall, H. Margolis, B. Kelly, D. Baldocchi, G. den Hartog, J. Cihlar, M.G. Ryan, B. Goodison, P. Crill, K.J. Ranson, D. Lettenmaier, and D.E. Wickland. 1995. The boreal ecosystem-atmosphere study (BOREAS): an overview and early results from the 1994 field year. Bulletin of the American Meteorological Society. 76(9):1549-1577.

Sellers, P.J., F.G. Hall, R.D. Kelly, A. Black, D. Baldocchi, J. Berry, M. Ryan, K.J. Ranson, P.M. Crill, D.P. Lettenmaier, H. Margolis, J. Cihlar, J. Newcomer, D. Fitzjarrald, P.G. Jarvis, S.T. Gower, D. Halliwell, D. Williams, B. Goodison, D.E. Wickland, and F.E. Guertin. 1997. BOREAS in 1997: Experiment Overview, Scientific Results and Future Directions. Journal of Geophysical Research 102(D24): 28,731-28,770.

Singh, A.N. and R.S. Dwived. 1986. The Utility of LANDSAT Imagery as an Integral Part of the Data Base for Small Scale Soil Mapping. Int. J. Remote Sensing. 7:1099-1108.

Taranik, J.V. 1978. Characteristics of the Landsat Multispectral Data System. U.S. Dept. of the Interior. Open File Report 78-187. Sioux Falls, SD.

Thompson, D.R. and O.A. Wehmanen. 1980. Using Landsat digital data to detect moisture stress in corn-soybean growing region. Photogr. Engr. & Rem. Sens. 46:1082-1089.

Williams, D.L., J.R. Irons, B.L. Markham, R.F. Nelson, D.L. Toll, R.S. Latty, and M.L. Stauffer. 1984. A statistical evaluation of the advantages of Landsat Thematic Mapper data in comparison to Multi-spectral Scanner data. IEEE Transactions on Geoscience and Remote Sensing. GE-22.

17.3 Archive/DBMS Usage Documentation None.

18. Glossary of Terms

None.

19. List of Acronyms

ASCII - American Standard Code for Information Interchange

BOREAS - BOReal Ecosystem-Atmosphere Study

BORIS - BOREAS Information System

BPI - Byte per inch - Band Sequential BSO

CCRS - Canada Centre for Remote Sensing

- Computer Compatible Tape CCT

CD-ROM - Compact Disk-Read-Only Memory DAAC - Distributed Active Archive Center

DAT - Digital Archive Tape

DN - Digital Number

EOS - Earth Observing System

EOSDIS - EOS Data and Information System ERTS - Earth Resources Technology Satellite

FOV - Field of View

FPAR - Fraction of Photosynthetically Active Radiation

GICS - Geocoded Image Correction System GIS - Geographic Information System GPS - Global Positioning System GSFC - Goddard Space Flight Center HTML - HyperText Markup Language
IFOV - Instantaneous Field of View

ΚT - Kauth-Thomas LAI - Leaf Area Index

LGSOWG - Landsat Ground Station Operations Working Group

LTWG - LGSOWG Technical Working Group

MSS - Multispectral Scanner

NAD27 - North American Datum of 1927 NAD83 - North American Datum of 1983

NASA - National Aeronautics and Space Administration

NE - Noise Equivalent
NSA - Northern Study Area
NTS - National Topographic System

ORNL - Oak Ridge National Laboratory PANP - Prince Albert National Park

RSI - Radarsat International RSS - Remote Sensing Science

SBRC - Santa Barbara Research Center SBRS - Santa Barbara Remote Sensing

SSA - Southern Study Area TE- Terrestrial Ecology TM - Thematic Mapper

URL - Uniform Resource Locator
UTM - Universal Transverse Mercator
WWW - World Wide Web

20. Document Information

20.1 Document Revision Dates

Written: 08-Oct-1998 Last Updated: 18-Aug-1999

20.2 Document Review Dates

BORIS Review: 03-Dec-1998

Science Review:

20.3 Document ID

20.4 Citation

When using these data, please include the following acknowledgment as well as citations of relevant papers in Section 17.2:

This data product was produced by the TE-18 team from Landsat TM data used in the BOREAS project. The Landsat TM images resulted from a joint development and processing effort between BOReal Ecosystem-Atmosphere Study (BOREAS) staff at the Canada Centre for Remote Sensing (CCRS) and the National Aeronautics and Space Administration (NASA) Goddard Space Flight Center (GSFC). The original level-3s and -3p data were acquired by CCRS and processed by RADARSAT International under an agreement with CCRS. The respective contributions of the above individuals and agencies to completing this data set are greatly appreciated.

If using data from the BOREAS CD-ROM series, also reference the data as:

Hall, F.G., "Regional-Scale Carbon Flux from Modeling and Remote Sensing." In Collected Data of The Boreal Ecosystem-Atmosphere Study. Eds. J. Newcomer, D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers. CD-ROM. NASA, 2000.

Also, cite the BOREAS CD-ROM set as:

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM. NASA, 2000.

20.5 Document Curator

20.6 Document URL

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE October 2000	3. REPORT TYPE AND DATES COVERED Technical Memorandum	
4. TITLE AND SUBTITLE	October 2000	reclinical fric	5. FUNDING NUMBERS
	5. FUNDING NUMBERS		
Technical Report Series on the Bo	•	• ` ` ′	
BOREAS TE-18, 30-m, Radiom	etrically Rectified Landsat	TM Imagery	923
6. AUTHOR(S)			RTOP: 923-462-33-01
Forrest G. Hall and David Kn	app		
Forrest G. Hall, Editor			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS (ES)			8. PEFORMING ORGANIZATION REPORT NUMBER
Goddard Space Flight Center			
Greenbelt, Maryland 20771			2000-03136-0
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS (ES)			10. SPONSORING / MONITORING AGENCY REPORT NUMBER
National Aeronautics and Space	Administration		TM-2000-209891
Washington, DC 20546-0001			Vol. 177
washington, 2 c 2cc to coor			VOI. 177
11. SUPPLEMENTARY NOTES			
D. Knapp: Raytheon ITSS, N	ASA Goddard Space Flig	ght Center, Greenb	elt, Maryland
			·
12a. DISTRIBUTION / AVAILABILITY STA	TEMENT		12b. DISTRIBUTION CODE
Unclassified-Unlimited			
Subject Category: 43			
Report available from the NASA	A Center for AeroSpace Inf	ormation,	
7121 Standard Drive, Hanover,	MD 21076-1320. (301) 62	1-0390.	

13. ABSTRACT (Maximum 200 words)

The BOREAS TE-18 team used a radiometric rectification process to produce standardized DN values for a series of Landsat TM images of the BOREAS SSA and NSA in order to compare images that were collected under different atmospheric conditions. The images for each study area were referenced to an image that had very clear atmospheric qualities. The reference image for the SSA was collected on 02-Sep-1994, while the reference image for the NSA was collected on 21-Jun-1995. The 23 rectified images cover the period of 07-Jul-1985 to 18-Sep-1994 in the SSA and from 22-Jun-1984 to 09-Jun-1994 in the NSA. Each of the reference scenes had coincident atmospheric optical thickness measurements made by RSS-11. The radiometric rectification process is described in more detail by Hall et al. (1991). The original Landsat TM data were received from CCRS for use in the BOREAS project. The data are stored in binary image-format files. Due to the nature of the radiometric rectification process and copyright issues, these full-resolution images may not be publicly distributed. However, a spatially degraded 60-m resolution version of the images is available on the BOREAS CD-ROM series. See Sections 15 and 16 for information about how to possibly acquire the full resolution data. Information about the full-resolution images is provided in an inventory listing on the CD-ROMs.

14. SUBJECT TERMS BOREAS, terrestrial eco	15. NUMBER OF PAGES 21		
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
Unclassified	Unclassified	Unclassified	UL